

Anticon® Antiglare Roofing Blanket

Refer to product table below for applicable product codes covered by this document

Issue **H**

Product Type & Application

Anticon® Antiglare is a Glasswool blanket with a medium (733 MD) or heavy duty (753 HD) reinforced, paper based, semi-reflective antiglare foil laminate adhered to one side. It is intended for use as metal roof insulation in Class 1 residential applications for hot and humid regions (e.g. NCC Climate Zone 1), where the antiglare foil is positioned facing upward to reduce vapour transmission into the roof space.

Compliance with the NCC

For use in Australia, when correctly specified and installed, this product provides the following compliance:

NCC 2022

- **Thermal** - Complies with NCC 2022 Volume 1 J4D3(1) and ABCB Housing Provisions Standard 2022 13.2.2(1). This product meets the requirements of the NCC through compliance with AS/NZS 4859.1.
- **Thermal Break** - Meets the requirements of NCC 2022 Volume 1 J3D5(1) and ABCB Housing Provisions Standard 2022 13.2.3(7). When crushed between metal roof sheet and framing members this product provides an R-value of R0.2.
- **Fire Hazard Properties** - Meets the requirements of the NCC 2022 Volume 1, S7C7 for insulation materials. When assessed to AS/NZS 1530.3 this product does not exceed the 'Spread of Flame' or 'Smoke Developed' indices of Table S7C7.
- **Weatherproofing and Condensation Control** - Facing material only meets the requirements of the NCC 2022 Volume 1 F3D3 and all State-prescribed variations, through compliance with AS/NZS 4200.1.
- **BAL** - All products meet the requirements for sheet roof construction of buildings in bushfire-prone regions BAL 12.5-40, as per AS 3959, sections 5 to 8.

NCC 2019

- **Thermal** - Complies with NCC 2019 Volume 1 Amend. 1 Section J1.2(a), NCC 2019 Volume 2 Amend. 1 Section 3.12.1.1(a), and all state-prescribed variations. The product meets the requirements of the NCC through compliance with AS/NZS 4859.1.
- **Thermal Break** - Meets the requirements of NCC 2019 Volume 1 Amend. 1 J0.4 and NCC 2019 Volume 2 Amend. 1 13.12.1.2(c). When crushed between metal roof sheet and framing members this product provides an R-value of R0.2.
- **Fire Hazard Properties** - Meets the requirements of the NCC 2019 Volume 1 Amend. 1, Specification C1.10 Clause 7 for insulation materials. When assessed to AS/NZS 1530.3 this product does not exceed the 'Spread of Flame' or 'Smoke Developed' indices of Specification C1.10 Clause 7.

Compliance with the NCC cont.

NCC 2019 cont.

- **Weatherproofing and Condensation Control** - Facing material only meets the requirements of the NCC 2019 Volume 1 Amend. 1 F1.6 and all State-prescribed variations, through compliance with AS/NZS 4200.1.
- **BAL** - All products meet the requirements for sheet roof construction of buildings in bushfire-prone regions BAL 12.5-40, as per AS 3959, sections 5 to 8.

Evidence of Suitability

- Testing to AS/NZS 4859.1 at 23°C across the following reports apply to the unfaced blanket -
 - CSR Lab Report R-20024.
 - CSR Lab Report R-20025.
 - CSR Lab Report R-20027.
 - CSR Lab Report R-20030.
- Testing to AS/NZS 4200.1 across the following reports apply to the **Medium Duty** facing product -
 - CSIRO Report 14-0242a - *Resistance to Dry Delamination.*
 - CSIRO Report 14-0242a - *Resistance to Wet Delamination.*
 - CSIRO Report 14-0242a - *Moisture Shrinkage.*
 - Orora Report 24133 - *Folding Endurance.*
 - CSIRO Report 14-0242a - *Tensile Strength.*
 - AWTATA Report 16-005483 - *Edge Tearing.*
 - R&D Services Report RD17304, RD17258 - *Emittance Classification.*
 - R&D Services Report RD18711-R2 - *Vapour Control Classification.*
 - AWTATA Report 7-578798-MV - *Water Control Classification.*
 - CSR Lab NATA Report NR-17211 - *Flammability Classification.*
 - CSR Lab Report R-20078 - *Thickness.*
- Testing to AS/NZS 4200.1 across the following reports apply to the **Heavy Duty** facing product -
 - AWTATA Report 18-000294 - *Resistance to Dry Delamination.*
 - AWTATA Report 18-000293 - *Resistance to Wet Delamination.*
 - AWTATA Report 18-000292 - *Moisture Shrinkage.*
 - Orora Report 24133 - *Folding Endurance.*
 - AWTATA Report 24-001259 - *Tensile Strength.*
 - AWTATA Report 24-001259 - *Edge Tearing.*
 - R&D Services Report RD17258 - *Emittance Classification.*
 - AWTATA Report 24-000131 - *Emittance Classification.*
 - R&D Services Report RD19028-R3 - *Vapour Control Classification.*
 - AWTATA Report 18-000295 - *Water Control Classification.*
 - CSR Lab NATA Report NR-17214 - *Flammability Classification.*
 - CSR Lab Report R-20078 - *Thickness.*
- Professional Assessment, AS/NZS 1530.3 -
 - Warringtonfire Assessment FAS200045.

Anticon® Antiglare Roofing Blanket

Specific Design or Installation Instructions

- Isolate power before installation.
- **WARNING:** This product contains aluminium foil which conducts electricity. To avoid electrocution, care should be taken to ensure that this product or conductive fasteners used to secure this product, do not come into contact or close proximity with electrical wiring during installation or use.
- **Caution:** Electrical cables and equipment partially or completely surrounded with bulk thermal insulation may overheat and fail. In new build construction with electrical wiring in accordance with AS/NZS 3000: 2018 or later, wiring may be partially or completely surrounded for up to 400mm. If more than 400mm is surrounded, or for wiring pre AS/NZS 3000:2018, seek advice from a licenced electrician. Refer to legislation and referenced standards for full details or seek advice from an electrician if in doubt.
- This product is intended for use in hot and humid regions (e.g. NCC climate zone 1) with the antiglare foil side positioned facing upward.
- **Condensation Risk Consideration:** The facing material is classified as a vapour barrier and is recommended to be positioned on the warm side of the construction to reduce the risk of condensation entrapment within the structure. This product is intended for installation with the antiglare facing material directed upwards, which in regions with mild-to-cold overnight temperatures (e.g. NCC Climate Zones 3-8) may position it on the cold side of the structure, making it unsuitable for installation in these regions. As there are many factors which can influence condensation risk it is highly recommended that designers undertake a hygrothermal analysis to further reduce condensation risk.
- Insulation should be installed so that it forms a continuous layer and abuts or overlaps adjoining insulation other than at supporting members such as columns, studs, noggings, joists, furring channels and the like where the insulation must butt against the member.
- **Thermal Break:** Where this product is locally crushed between framing members and roof cladding it will provide a R0.2 thermal break as required by the NCC.
- Bulk insulation must be installed so that it maintains its position and thickness, other than where it crosses water pipes, electrical cabling or the like, or roof battens in Class 1 and 10 buildings, cladding and supporting members in Class 2-9 buildings, or where accounted for elsewhere.
- Stated thermal performance is based on bulk insulation only. The effects of thermal bridging and any added reflective R-value contributions are construction dependent and must be determined in the accordance with AS/NZS 4859.2.
- To create an air, water, or vapour barrier install in accordance with the NCC and AS 4200.2.
- To maintain the water barrier properties of the facing material it should not be punctured, creased, crushed, sharply folded or dragged over the building structure during installation.

Specific Design or Installation Instructions cont.

- Suitable for applications where the product is protected from direct UV light, water and wind pressure during and after installation.

For general installation guidance refer to the product installation guide at Bradfordinsulation.com.au

Supplementary information - Additional installation guidance for this product can be found in AS 3999.

Limitations of Use

- **IMPORTANT:** Compliance with the evidence of suitability data referenced in this document is only achieved when this product is produced at a CSR approved facility, in accordance with CSR specifications and approved materials.
- **IMPORTANT:** Do Not Modify This Product: Compliance with the evidence of suitability data referenced in this document is only achieved by the product or configuration listed in this PTS.
- This material is not classified as non-combustible in accordance with AS1530.1 and is not suitable for use where non-combustible material is required.
- This product does not meet the non-combustibility or fusion temperature requirements of AS 1668.1 – The use of ventilation and air conditioning in buildings, 2.3.2.
- This product is not suitable for use as an exposed internal wall or ceiling lining in applications which require a Group Number in accordance with AS ISO 9705 and AS 5637.1 (NCC 2019 Volume 1 Amend. 1, Specification C1.10 Clause 4, NCC 2022 Volume 1 S7C4).
- Maximum service temperature is 150°C for unfaced Glasswool, 70°C for faced Glasswool.
- This product is not designed to withstand exposure to the elements and must be installed dry and remain dry until the roof is completed - accordingly, it is recommended that the exterior cladding and all closure flashings should be installed within the same workday to comply with the product warranty.
- It is recommended to commence installation of this product only if it can be completed prior to rain.
- If this product is left exposed, it must be protected from getting wet.
- Not recommended for use with concrete, terracotta or slate tile roofs.
- Not suitable for use in mild-to-cold regions (e.g. NCC Climate Zones 3-8).
- The foil facing product should not come into contact with wet concrete, or alkaline materials.
- This product is not suitable for installation in underslab concrete roof applications within a conditioned space where there is a risk of moisture transfer through the unfaced edges.

Anticon® Antiglare Roofing Blanket

Conditions of Storage, Use & Maintenance

- Store in the original packaging in a cool, dry area, away from foodstuffs. Ensure packages are adequately labelled, protected from physical damage, and sealed when not in use. Avoid packaging being stored under UV light (direct sunlight) for long periods. Store in the original packaging in a cool, dry area, removed from UV light (direct sunlight).
- Do not pressure clean or use mineral based cleaners on the facing product.

Refer to the product SUI/MSDS at Bradfordinsulation.com.au for more information.

Applicable Product Codes

R-VALUE [m ² K/W]	THICKNESS [mm]	NOMINAL LENGTH [m]	NOMINAL WIDTH [mm]	NOMINAL COVERAGE [m ² per Roll]	PRODUCT	PRODUCT CODE
MEDIUM DUTY FACING						
R1.3	60	15	1200	18	Anticon® 60	15860
R1.8	80	10	1200	12	Anticon® 80	17632
R2.3	100	10	1200	12	Anticon® 100	17631
HEAVY DUTY FACING						
R1.3	60	15	1200	18	Anticon® 60	96078
R1.8	80	10	1200	12	Anticon® 80	96079
R2.3	100	10	1200	12	Anticon® 100	96080
R3.0	130	10	1200	12	Anticon® 130	113584

Material R-values are determined in accordance with AS/NZS 4859.1 at 23°C. The contribution of the reflective air-gap is construction dependant and excluded from the declared R-value. The duty classification of the facing material does not influence the R-value.

Additional Product Data

Maximum Service Temperature		<ul style="list-style-type: none"> • 150°C for Unfaced Glasswool • 70°C for Faced Glasswool
Volatile Organic Compound (VOC) and Formaldehyde Emissions	When tested in accordance with ASTM D5116	<ul style="list-style-type: none"> • VOC 0.122 mg/m²/hr • Formaldehyde 0.035 mg/m²/h

Other Accreditation



FBS-1 Glasswool - The fibre component of these products is listed by Safe Work Australia as Man-made Vitreous Fibre (Glasswool) of low bio persistence as specified under Note Q in the Australian Hazardous Substances Information System and in the Australian Approved Criteria documentation. In accordance with EU ATP 31 (2009) these fibres are not classified as an irritant, or as carcinogenic.
Refer to the product SUI/MSDS at Bradfordinsulation.com.au for more information.



National Asthma Council Sensitive Choice